



SATA GmbH & Co. KG • Postfach 1828 • 70799 Kornwestheim

To Whom It May Concern

G. Drakos

+49 (71 54) 8 11-4 72

+49 (71 54) 8 11-1 90

georg.drakos@sata.com

8. November 2010

It is our pleasure to confirm that the following SATA spray guns do comply with HVLP mandates; namely that they show maximum 10 psi air cap pressure at recommended spray gun inlet pressure highlighted in the operating manuals. The transfer efficiency of all listed SATA HVLP spray guns is larger 65 % provided the spray gun is set-up by the user with the recommended inlet pressure and spray distance shown in the operating manuals.

SATAjet® B NR 95	maximum spray gun inlet pressure:	43 psi
SATAjet® K NR 95	maximum spray gun inlet pressure:	43 psi
SATAminijet® NR	maximum spray gun inlet pressure:	43 psi
SATAminijet® 2 HVLP	maximum spray gun inlet pressure:	29 psi
SATAminijet® 3 HVLP	maximum spray gun inlet pressure:	29 psi
SATAminijet® 4 HVLP	maximum spray gun inlet pressure:	29 psi
SATAjet® 2000 HVLP	maximum spray gun inlet pressure:	29 psi
SATAjet® 2000 HVLP DIGITAL® 2	maximum spray gun inlet pressure:	29 psi
SATAjet® 3000 HVLP	maximum spray gun inlet pressure:	29 psi
SATAjet® 3000 HVLP DIGITAL®	maximum spray gun inlet pressure:	29 psi
SATAjet® 3000 B HVLP	maximum spray gun inlet pressure:	29 psi
SATAjet® 3000 B HVLP DIGITAL®	maximum spray gun inlet pressure:	29 psi
SATAjet® 4000 B HVLP	maximum spray gun inlet pressure:	29 psi
SATAjet® 4000 B HVLP DIGITAL®	maximum spray gun inlet pressure:	29 psi
SATAjet® K3™ HVLP	maximum spray gun inlet pressure:	36 psi
SATAjet® K3™ HVLP DIGITAL®	maximum spray gun inlet pressure:	36 psi
SATA® KLC™ HVLP	maximum spray gun inlet pressure:	29 psi
SATA® LM™ 2000 B HVLP	maximum spray gun inlet pressure:	43 psi
SATA® LM™ 2000 H HVLP	maximum spray gun inlet pressure:	43 psi
SATA® LM™ 2000 K HVLP	maximum spray gun inlet pressure:	43 psi
SATA® LP™ jet K3™ HVLP	maximum spray gun inlet pressure:	58 psi
SATA® LP™ jet K3™ HVLP ROB™	max. round air inlet pressure:	42 psi
	max. flat air inlet pressure:	48 psi
SATAjet® 90-2 HVLP	maximum spray gun inlet pressure:	29 psi
SATAjet® 1000 K™ HVLP	maximum spray gun inlet pressure:	36 psi
SATAjet® 100 HVLP	maximum spray gun inlet pressure:	29 psi
SATAjet® 1000 B HVLP	maximum spray gun inlet pressure:	29 psi

SATA GmbH & Co. KG
R&D Department


i. V. Dr. Ewald Schmon


i. V. Jörg Göttling

Hausanschrift:
Domenialstr. 28 • 70806 Kornwestheim
Telefon +49 71 54 6 11-0
Fax Verkauf 196 • Export 194 • Einkauf 192
E-Mail: info@sata.com
Internet: www.sata.com

Bankverbindungen:
Commerzbank Ludwigsburg (BLZ 604 400 23) Kto. 1 020 901
BIC COBADE33XXX • IBAN DE35 6044 0073 0702 2001 00
Kreissparkasse Ludwigsburg (BLZ 604 300 50) Kto. 25 669
BIC SOLADE33LGB • IBAN DE10 6045 0050 0001 0256 00
BW-Bank Ludwigsburg (BLZ 600 501 01) Kto. 1 032 500 403
BIC SOLADE33 • IBAN DE04 6005 0101 7832 5004 03

Konsumbündelgesellschaft mit Sitz in Kornwestheim
Registriergericht: Stuttgart HRA 202191
Persönlich haftende Gesellschafterin
SATA Verwaltungs GmbH, Kornwestheim, 8999 0010
Geschäftsführer: Albrecht Kruse, Stuttgart
JSt-IdNr. DE 146132516

